

Product Datasheet

Alumasc Acrylic Brick Slips

Sheet No: PD703FA

Issued: October 2012

Pages: 1 of 2

Description

Alumasc Acrylic Brick Slips are 4mm thick brick slips available in both stretcher and corner 'pistols' forms.

Use

Alumasc Acrylic Brick Slips are used as the finish to the Alumasc Acrylic Brick Slip System. They are used in order to replicate a brick facade. They can be used as a complete system finish or as a complementary finish with the Alumasc suite of finishing renders.

General Performance

Alumasc Acrylic Brick Slips offer a lightweight facade finish. They can be used for complete floors or as features such as string and soldier courses as well as corner and quoin features. Alumasc Acrylic Brick Slips are a high performing finish used in both Alumasc External Wall Insulation (EWI) and Render Only (RO) systems.

Approvals

Alumasc Acrylic Brick Slips are approved for use as a brick only finish or as the final layer of an Alumasc Swisitherm External Wall Insulation system. Can be used in high rise situations.

Colours

Various shades and textures (please refer to our website for further details). Specific colour matches are available. Please contact Alumasc technical for further information.

Thickness

4mm

Coverage

Stretcher bricks = 60 bricks per m² (based on standard UK brick sizes)

Corner bricks 'Pistols' = 14 per lin m (based on standard UK brick sizes)

Protection

Not applicable

Weight

Stretcher bricks = 6kgs/m²

Corner bricks 'Pistols' = 2.1kgs/lin m

Application

Alumasc Acrylic Brick Slips are applied directly on to the Alumasc Acrylic Brick Slip Adhesive. The bricks are offered up to the adhesive and pushed in to place by hand to the desired spacing. The bricks should be applied from the top down to avoid and damage or staining from progressive work. The adhesive between the bricks is smoothed with an artist's brush or similar to create the mortar joints. Alumasc Acrylic Brick Slips should not be applied in cold/frost conditions as they will become brittle and be difficult to install.

It is advisable to use bricks from multiple boxes to ensure integration of colour variances as encountered with real bricks.

Mixing Ratio

Not applicable.

Fire Rating

Class 0 surface spread of flame.

Product Datasheet

Alumasc Acrylic Brick Slips

Sheet No: PD703FA

Issued: October 2012

Pages: 2 of 2

Pack Size

Alumasc Acrylic Brick Slips are supplied in boxes of;

Stretcher bricks = 118 slips per box

Corner bricks 'Pistols' = 26 slips per box

Storage

Alumasc Acrylic Brick Slips should be stored off the floor in a dry place. Exposure to frost will cause the bricks to become brittle.

Health & Safety

Safety Data Sheets are available upon request, and can also be downloaded directly from:

www.alumascfacades.co.uk

Technical Support

Technical advice is available from Alumasc Technical Services at:

Telephone: +44 (0)1744 648400

Facsimile: +44 (0)1744 648401

Email: technical@alumasc-exteriors.co.uk

The company pursues a policy of constant product development and information contained in this publication is therefore subject to change without notice. The customer is responsible for ensuring that each product is fit for its intended purpose and that the conditions for use are suitable. All quoted data is nominal and subject to production tolerances.